

Whatsapp: +31 6 838 621 62
info@elektromotor.nl

Model No. 4-Pole cage motor MAP 180M 18,5kW D400V 50Hz IM3041-FF300

Table with 15 columns: U (V), Δ/Y Conn, f [Hz], P [kW], P [hp], I [A], n [RPM], T [Nm], IE Class, % EFF at __ load (FL, 3/4FL, 1/2FL), PF at __ load (FL, 3/4FL, 1/2FL), IA/IN [pu], TA/TN [pu], TK/TN [pu].

Table with 2 columns: Property and Value. Properties include Motor type, Enclosure, Frame Material, Frame size, Duty, Voltage, Frequency, Power output, Insulation class, Ambient temperature, Temperature rise, Temperature rise surface, Altitude above sea level, Hazardous area classification.

Table with 2 columns: Property and Value. Properties include Rotor type, Bearing type.

Table with 2 columns: Property and Value. Property: Type of grease. Value: 0.

Table with 2 columns: Property and Value. Property: Country of origin. Value: TR.

Table with 6 columns: Voltage/Freq, Locked rotor Torque [% nom], Starting current [% nom], Pull-up Torque [% nom], Breakdown Torque [% nom], No-load Current [A].

NOTE
All performance values at rated voltage and frequency.
All performance parameters are subjected to standard tolerance as per IEC 60034-1
Voltage, Frequency are as per IEC60034-1
Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Table with 2 columns: Property and Value. Properties include Efficiency, Standards.

Table with 2 columns: Property and Value. Properties include Degree of protection, Mounting type, Cooling method, Motor weight - approx., Gross weight - approx., Motor inertia, Vibration level, Direction of rotation, PTC.



V2.08 18-7-2024 16:10